



SCHEDA TECNICA DEL SISTEMA - SYSTEM TECHNICAL CARD

SERIE: Verandha 45

PROFILATI estrusi lega: 6060 (UNI 9006/1).

TOLLERANZE DIMENSIONALI E SPESSORI: UNI EN 12020-02

TIPO DI TENUTA ARIA ACQUA: a battente.

APPLICAZIONI VETRO: con fermavetro a taglio 45° squadrato o a taglio 90° arrotondato.

CAMERA PER VETRO: variabile secondo i fermavetri usati.

DIMENSIONE BASE DEL SISTEMA:

Telaio: sez. 52 mm.

Anta: sez. 45 mm.

Fuga tra telaio laterale e anta: 10/12,5 mm.

Fuga tra telaio superiore/inferiore e anta: 12,5 mm.

Fuga sul nodo centrale: 10 mm.

Aletta battuta vetro: 21 mm.

IMPIEGO: il sistema permette la realizzazione di verande a libro con ante sospese : a fermavetro, a vetro infilare e con persiana.

SERIES: Verandha 45

MATERIAL ALLOY: 6060 (UNI 9006/1)

DEVIATION IN DIMENSION AND FORM: UNI EN 12020-02

AIR-WATER SEAL TYPE: overlap.

GLASS APPLICATIONS: with normal or rounded glass holder with cuts at 45 or 90 degrees.

GLASS CHAMBER: variable according to the profiles used.

BASIC DIMENSIONS OF THE SYSTEM:

Frame section : 52 mm.

Wing section : 45 mm.

Space between lateral frame and wing : 10/12,5 mm.

Space between upper/lower frame and wing : 12,5 mm.

Space on central nucleus mm. 10.

Flap of glass rabbet mm. 21.

USAGE: the system allows the realization of: book verandas with poised wings : with glasskeeper, insert glass and shutter wing.